



SideWinder Angle Blast Nozzles



Product Features

PanBlast™ SideWinder Angle Nozzles are designed for blasting areas that would normally be inaccessible with conventional blast nozzles. Nozzle outlets are located on the side, at a 45° angle, to reach behind and inside components. This series includes nozzles with single and multiple outlets as well as a wide range of sizes.

- ▶ Lightweight, durable aluminum jacket.
- ▶ Rugged, water-resistant tungsten carbide sleeve.
- ▶ 1 or 3 outlet configuration.
- ▶ Size #4 (6 mm , 1/4"), #5 (8 mm , 5/16") and #6 (10 mm , 3/8") available.
- ▶ Available with 50 mm (2") coarse and 30 mm (1-1/4") fine threads.

Common Applications

- ▶ Internal pipe cleaning operations.
- ▶ Blasting under ledges and other protrusions.
- ▶ Large or small blast pot operations.

Complementary Products



Pressure Blast Pots



Nylon Nozzle Holders



Aluminum Nozzle Holders



AirFlo Pneumatic Handle



Blast Hoses



Nylon Couplings



Steel Couplings



Nozzle Washers



PanBlast™ SideWinder Angle Blast Nozzles

Stock Code	Description	Orifice Size	No. of Outlets	Thread Size	Entry Size	Blast Angle
BAC-NZ-PB-0291	Blast Nozzle SideWinder 4x1 2" UNC	6 mm (1/4")	1	50 mm (2")	25 mm (1")	45°
BAC-NZ-PB-0292	Blast Nozzle SideWinder 4x3 2" UNC	6 mm (1/4")	3			
BAC-NZ-PB-0293	Blast Nozzle SideWinder 5x1 2" UNC	8 mm (5/16")	1			
BAC-NZ-PB-0294	Blast Nozzle SideWinder 5x3 2" UNC	8 mm (5/16")	3			
BAC-NZ-PB-0295	Blast Nozzle SideWinder 6x1 2" UNC	10 mm (3/8")	1			
BAC-NZ-PB-0296	Blast Nozzle SideWinder 6x3 2" UNC	10 mm (3/8")	3			
BAC-NZ-PB-0299	Blast Nozzle SideWinder 4x1 1-1/4" NPSM	6 mm (1/4")	1	32 mm (1-1/4")	25 mm (1")	45°
BAC-NZ-PB-0300	Blast Nozzle SideWinder 4x3 1-1/4" NPSM	6 mm (1/4")	3			
BAC-NZ-PB-0301	Blast Nozzle SideWinder 5x1 1-1/4" NPSM	8 mm (5/16")	1			
BAC-NZ-PB-0302	Blast Nozzle SideWinder 5x3 1-1/4" NPSM	8 mm (5/16")	3			
BAC-NZ-PB-0303	Blast Nozzle SideWinder 6x1 1-1/4" NPSM	10 mm (3/8")	1			
BAC-NZ-PB-0304	Blast Nozzle SideWinder 6x3 1-1/4" NPSM	10 mm (3/8")	3			